



BASIC

BREATHABLE WATER-BASED PAINT



MAIN PROPERTIES

- **Good breathability and coverage**
- **Suitable mainly for painting industrial buildings**
- **Non-film-forming, matte effect**
- **For indoor use**

Breathable water-based paint, **for indoor use**. Good coverage and easy to spread, for economical finishing cycles. Thanks to these characteristics, it does not crack or peel away even in damp environments.

USAGE INDICATIONS

Suitable for use on ceilings in private residences or public buildings and for internal use in industrial buildings requiring good breathability and coverage.

PREPARING THE SURFACE

On new plaster: leave to cure completely for at least 28 days. Brush to remove any uneven parts on the surface, and if necessary, smooth out using plaster. Sand down any excess plaster and then apply MISTER SMALTO. Apply a pre-coat of FIX ACRYL to consolidate the surface, on difficult surfaces or to ensure even absorption in the case of colour topcoats. If mould or algae are present, pre-treat the surface with biocidal solutions such as MUFFA BLOCK.

To touch up plasterwork: prepare the surface by removing traces of loose paint, dirt and mould. If necessary, level out any inconsistencies with plaster. Sand down any excess plaster before applying MISTER SMALTO. Apply a pre-coat of FIX ACRYL to consolidate the surface, on difficult surfaces or to ensure even absorption in the case of colour topcoats. If mould or algae are present, pre-treat the surface with biocidal solutions such as MUFFA BLOCK.

TECHNICAL CHARACTERISTICS

Type of binder:	Synthetic copolymers in emulsion
Colour:	White
Appearance:	Thixotropic
Appearance of the film:	Matte
Specific weight:	Kg/l 1.600 ± 0.04
VOC:	< 30 (Directive 2004/42/CE) - (cat. A/a/BA) Max. 30 g/l (2010)
Yield:	4 - 5 m ² /l finished work (2 coats)



BASIC

BREATHABLE WATER-BASED PAINT



INDICATIONS FOR APPLICATION

Do not apply where there is surface condensation.

Ambient temperature: minimum + 5 °C – maximum +35 °C

Surface temperature: minimum + 5 °C – maximum +35°C

The product can be applied:

With a brush or roller: dilute with water 20/30%

With a spray: dilute with water 40/50%

Cleaning of tools: wash with water immediately after use.

DRYING OR HARDENING AT 20°C AND WITH 65 % R.U. (relative humidity)

Touch dry time: 1 h

Apparent complete drying time: 4 - 6 h

Can be varnished over after: 6 - 8 h

PACKS

14 L

STORAGE

The product must be stored in the original containers, tightly closed, and remains stable for at least 12 months, provided it is stored at a temperature of between +5°C and +40°C.

Frost sensitive

SAFETY INSTRUCTIONS

Pursuant to Directive 67/548/CEE, 1999/45/CE and/or Regulation 1272/2008 (CLP) as amended, the product is not labelled. For full information on handling the product and how to dispose of it correctly, please refer to the Safety Sheet.