



# **FIX ACRYL**

## **ACRYLIC FIXATIVE**



### MAIN PROPERTIES

- Evens out surface absorption
- Water-soluble
- Adhesion promoter
- For indoor and outdoor use

FIX ACRYL is a special acrylic resin solution that can be used, when diluted into 1:4 – 1:6 parts (1 part product and 4 or 6 parts water), as a superficial impregnation coat of brickwork surfaces, evenly spreading and reducing absorption and improving grip of subsequent finishes.

### USAGE INDICATIONS

The product is indicated for use on various types of plasterwork; roughcast, two-coat plasterwork, gypsum, plasterboard, and for old paintwork and organic or mineral, dry and compact absorbent finishes.

### PREPARING THE SURFACE

Once all traces of dirt and mould have been removed, if required use STUCCA TUTTO for smoothing, sand and remove dust, then apply FIX ACRYL.

After application, the wall should not have a shiny appearance, as the product should penetrate into the surface without a film forming. Particularly outdoors, on crumbling, dusty, or poorly compact or reactive paintwork, it is preferable to make the product penetrate as much as possible. Diluted product yield: 8/10 mq/l per coat (variable depending on absorption). Drying time: 4 hours approximately. It is recommended applying the first coat of water-based paint maximum 24-48 hours after applying FIX ACRYL.

### TECHNICAL CHARACTERISTICS

Type of binder:	Styrene resin - acrylic
Colour:	Opalescent
Appearance:	Liquid
Appearance of the film:	Transparent
Specific weight:	Kg/l 1.025 ± 0.04
VOC:	< 30 (Directive 2004/42/CE) - (cat. A/a/BA) Max. 30 g/l (2010)
Diluted product yield:	8-10 mq/l per coat (depending on the absorption of the medium).



# **FIX ACRYL**

## **ACRYLIC FIXATIVE**



### **INDICATIONS FOR APPLICATION**

Ambient conditions and surface conditions: Do not apply where there is surface condensation or direct sunlight.

Ambient temperature:	Minimum + 5° C – Maximum +35° C
Surface temperature:	Minimum + 5° C – Maximum +35° C
The product can be applied:	With a paintbrush - roller - Spray bottle: dilute with water into 1 part fixative, 4/6 parts water.
Cleaning of tools:	wash with water immediately after use.

### **DRYING OR HARDENING AT 20°C AND WITH 65 % R.U. (relative humidity)**

Touch dry time	30 - 60 minutes
Paintability time	4h

### **PACKS**

1 L and 5 L

### **STORAGE**

When the product is stored in its original, tightly sealed containers it will remain stable for at least 12 months, provided it is stored at a temperature of between +5°C and +40°C.  
Frost sensitive

### **SAFETY INSTRUCTIONS**

Pursuant to Directive 67/548/CEE, 1999/45/CE and/or Regulation 1272/2008 (CLP) as amended, the product is not labelled. For full information on handling the product and how to dispose of it correctly, please refer to the Safety Sheet.