



# MISTER GAP

## PAINTABLE ACRYLIC SEALANT



### MAIN PROPERTIES

- **Paintable**
- **Excellent surface adherence**
- **For indoor and outdoor use**
- **Ready for use**

Professional single-component acrylic resin-based sealant in a water medium.

### USAGE INDICATIONS

This product is used to seal internal and external connecting joints of construction elements under medium stress conditions, and for filling in cracks and for building touch ups. It adheres to porous and smooth surfaces as well as damp surfaces such as concrete, cement, brickwork, paintwork, asbestos and wood.

### PREPARATION OF THE SURFACE AND PRODUCT APPLICATION

Remove all traces of dirt and mould and apply Mister GAP evenly across the whole joint, covering it completely without leaving any clear areas.

It is recommended shielding the product from the rain for at least 6 hours

### TECHNICAL CHARACTERISTICS

Type of binder:	Acrylic resin
Colour:	White
Appearance:	Paste
Extension:	8% of the length of the joint
Specific weight:	Kg/l 1.6 ± 0.04
Polymerisation:	Through atmospheric moisture



# **MISTER GAP**

## **PAINTABLE ACRYLIC SEALANT**



### **INDICATIONS FOR APPLICATION**

Ambient conditions and surface conditions: Do not apply where there is surface condensation or direct sunlight.

Ambient temperature:	Minimum + 5° C – Maximum +40° C
Surface temperature:	Minimum + 5° C – Maximum +40° C
The product can be applied:	Cartridge applicator

Cleaning of tools: wash with water immediately after use.

### **DRYING OR HARDENING AT 20°C AND WITH 65 % R.U. (relative humidity)**

Touch dry time	60 - 90 minutes
Total polymerisation time	1 - 3 weeks (depending on the thickness applied)
Paintability time	12/24h

### **PACKS**

310 ml Cartridges  
Boxes of 24 units

### **STORAGE**

When the product is stored in its original, tightly sealed containers it will remain stable for at least 12 months, provided it is stored at a temperature of between +5°C and +40°C.  
Frost sensitive

### **SAFETY INSTRUCTIONS**

Pursuant to Directive 67/548/CEE, 1999/45/CE and/or Regulation 1272/2008 (CLP) as amended, the product is not labelled. For full information on handling the product and how to dispose of it correctly, please refer to the Safety Sheet.