



# TOP

## PROFESSIONAL BREATHABLE WATER-BASED PAINT



### MAIN PROPERTIES

- Excellent breathability and coverage
- Suitable for indoor use
- Non-film-forming effect
- Excellent whiteness

TOP is a professional, water-based paint **for indoor use**. Excellent breathability and coverage. Formulated with vinyl resins and titanium for excellent whiteness.

Thanks to these characteristics, it does not crack or peel away even in damp environments.

### USAGE INDICATIONS

Suitable for walls and ceilings to guarantee perfect breathability, even in damp conditions. This water-based paint is particularly suitable for kitchens, bathrooms and cellars. It can be used for painting, also spray painting, the interior of buildings to obtain a quality non-powder finish.

### PREPARING THE SURFACE

**On new plaster:** leave to cure completely for at least 28 days. Brush to remove any uneven parts on the surface, and if necessary, smooth out using plaster. Sand down any excess plaster before applying MISTER SMALTO. Apply a pre-coat of FIX ACRYL to consolidate the surface, on difficult surfaces or to ensure even absorption in the case of colour topcoats. If mould or algae are present, pre-treat the surface with biocidal solutions such as MUFFA BLOCK.

**To touch up plasterwork:** prepare the surface by removing traces of loose paint, dirt and mould. If necessary, level out any inconsistencies with plaster. Sand down any excess plaster before applying MISTER SMALTO. Apply a pre-coat of FIX ACRYL to consolidate the surface, on difficult surfaces or to ensure even absorption in the case of colour topcoats. If mould or algae are present, pre-treat the surface with biocidal solutions such as MUFFA BLOCK.

### TECHNICAL CHARACTERISTICS

Type of binder:	Synthetic copolymers in emulsion
Colour:	White
Appearance:	Thixotropic
Appearance of the film:	Matte
Specific weight:	Kg/l 1.600 ± 0.04
VOC:	< 30 (Directive 2004/42/CE) - (cat. A/a/BA) Max. 30 g/l (2010)
Yield:	5 m <sup>2</sup> /l finished work (2 coats)



# TOP

## PROFESSIONAL BREATHABLE WATER-BASED PAINT



### CLASSIFICATION UNI EN 13300:

Granulometry (EN 21524 - ISO 787-7)	Fine
Wet scrub resistance (UNI EN ISO 11998)	Class 5
Gloss (EN ISO 2813)	13.8
Determination of contrast (EN ISO 6504-3)	Class 3

### INDICATIONS FOR APPLICATION

Do not apply where there is surface condensation or direct sunlight.  
Ambient temperature: minimum + 5 °C – maximum +35 °C  
Surface temperature: minimum + 5 °C – maximum +35°C

The product can be applied:  
With a brush or roller: dilute with water 25/35%  
With a spray: dilute with water 40/50%

Cleaning of tools: wash with water immediately after use.

### DRYING OR HARDENING AT 20°C AND WITH 65 % R.U. (relative humidity)

Touch dry time: 1 h  
Apparent complete drying time: 4 - 6 h  
Can be varnished over after: 6 - 8 h

### PACKS

5 L and 14 L

### STORAGE

The product must be stored in the original containers, tightly closed, and remains stable for at least 12 months, provided it is stored at a temperature of between +5°C and +40°C.  
Frost sensitive

### SAFETY INSTRUCTIONS

Pursuant to Directive 67/548/CEE, 1999/45/CE and/or Regulation 1272/2008 (CLP) as amended, the product is not labelled. For full information on handling the product and how to dispose of it correctly, please refer to the Safety Sheet.

